Uniform Mitigation Verification Inspection Form opy of this form and any documentation provided with the insu

			y of this form and	any documentation prov	vided with the insurance	ce policy			
-	_	tion Date: 2025-01-13							
		r Information							
		Name:				Contact Person:			
		ss: 528 Bristle Cone Ln				Home Phone:			
_		Naples	Zip: 34113		Work Phone:				
		y: Collier			Cell Phone:				
		nce Company:			Policy #:				
Ye	ear o	f Home: 1976	# of Stories:	1	Email:				
ac th	com ougl	2: Any documentation used in pany this form. At least one in 7. The insurer may ask ad	photograph must ac ditional questions re	ecompany this form to valid garding the mitigated featu	late each attribute marke re(s) verified on this form	ed in questions 3 n.			
1.		Building Code: Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)? A. Built in compliance with the FBC: Year Built For homes built in 2002/2003 provide a permit application with a date after 3/1/2002: Building Permit Application Date (MM/DD/YYYY) B. For the HVHZ Only: Built in compliance with the SFBC-94: Year Built For homes built in 1994, 1995, and 1996 provide a permit application with a date after 9/1/1994: Building Permit Application Date (MM/DD/YYYY) C. Unknown or does not meet the requirements of Answer "A" or "B"							
2.	Ro OR	of Covering: Select all roof of Year of Original Installation/vering identified.	overing types in use. I	Provide the permit application					
		2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance			
		✓ 1. Asphalt/Fiberglass Shingle	09/02/2015	20150928245	2015				
		2. Concrete/Clay Tile							
		3. Metal							
		4. Built Up							
		5. Membrane							
			09/02/2015	20150928245	2015				
	 □ A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later. □ B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later. □ C. One or more roof coverings do not meet the requirements of Answer "A" or "B". □ D. No roof coverings meet the requirements of Answer "A" or "B". 								
3.	Ro	of Deck Attachment: What is	s the weakest form of	roof deck attachment?					
	A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c. by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.								
	B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesive other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails space a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.								
		C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Grooved decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent							

Inspectors Initials Property Address 528 Bristle Cone Ln, Naples, FL 34113

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure, or inaccuracies found on the form.

		or greater resi 182 psf.	stance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least		
□ D. Reinforced Concrete Roof Deck.					
			or unidentified.		
		G. No attic ac			
4.	5 fe	eet of the inside	achment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within e or outside corner of the roof in determination of WEAKEST type)		
	~	A. Toe Nails	To a to fine and to the state of the state o		
			Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or		
			Metal connectors that do not meet the minimal conditions or requirements of B, C, or D		
	Mi	<u>nimal conditio</u>	ns to qualify for categories B, C, or D. All visible metal connectors are:		
			Secured to truss/rafter with a minimum of three (3) nails, and		
			Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.		
		B. Clips			
			Metal connectors that do not wrap over the top of the truss/rafter, or		
			Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.		
		C. Single Wra	Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.		
		D. Double W			
			Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or		
			Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.		
		E. Structural	Anchor bolts structurally connected or reinforced concrete roof.		
		F. Other:			
		G. Unknown	or unidentified		
		H. No attic ac	ccess		
5.			What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).		
		A. Hip Roof	Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: feet; Total roof system perimeter: feet		
		B. Flat Roof	Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft		
	•	C. Other Roo			
6.	Sec	condary Water	Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR)		
		sheathing	o called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the rom water intrusion in the event of roof covering loss.		
		B. No SWR.	or undetermined.		
In	spec	tors Initials	Property Address 528 Bristle Cone Ln, Naples, FL 34113		
*T	his	verification fo	rm is valid for up to five (5) years provided no material changes have been made to the structure or		

Page 2 of 4

inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.			Glazed Openings				Non-Glazed Openings	
			Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors	
N/A	Not Applicable- there are no openings of this type on the structure		\times	\times	\times		\times	
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)							
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)							
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007							
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance							
N	Opening Protection products that appear to be A or B but are not verified							
IN	Other protective coverings that cannot be identified as A, B, or C							
Х	No Windborne Debris Protection	\square				\square		

- A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).
 - Miami-Dade County PA 201, 202, and 203
 - Florida Building Code Testing Application Standard (TAS) 201, 202, and 203

A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist

- American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
- Southern Standards Technical Document (SSTD) 12
- For Skylights Only: ASTM E 1886 and ASTM E 1996
- For Garage Doors Only: ANSI/DASMA 115

	X in the table above				
	☐ A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above				
B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection of in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):					
	• ASTM E 1886 and ASTM E 1996 (Large Missile – 4.5 lb.)				
	• SSTD 12 (Large Missile – 4 lb. to 8 lb.)				
	• For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.)				
	B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist				

A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or

☐ B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above

B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above

C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).

C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist

C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above

 \square C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials Property Address 528 Bristle Cone Ln, Naples, FL 34113

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter sprotective coverings not meeting the requirements of An with no documentation of compliance (Level N in the ta	nswer "A", "B", or C" or sys				
□ N.1 All Non-Glazed openings classified as Level A, B, C, o	· · · · · · · · · · · · · · · · · · ·	n-Glazed	openings exist		
N.2 One or More Non-Glazed openings classified as Level table above					
N.3 One or More Non-Glazed openings is classified as Level	el X in the table above				
✓ X. None or Some Glazed Openings One or more Glaze	ed openings classified and Le	evel X in	the table above.		
MITIGATION INSPECTIONS MUST B Section 627.711(2), Florida Statutes, provi					
Qualified Inspector Name: Nick Brugal	License Type: Home Inspecto	or	License or Certificate #: HI9057		
Inspection Company: Patriot Home Inspections		Phone: 2	39-826-5866		
Qualified Inspector – I hold an active license as a	: (check one)				
Home inspector licensed under Section 468.8314, Florida Statute training approved by the Construction Industry Licensing Board Building code inspector certified under Section 468.607, Florida General, building or residential contractor licensed under Section	es who has completed the statute and completion of a proficiency Statutes.		er of hours of hurricane mitigation		
Professional engineer licensed under Section 471.015, Florida St	atutes.				
☐ Professional architect licensed under Section 481.213, Florida St	atutes.				
Any other individual or entity recognized by the insurer as posse verification form pursuant to Section 627.711(2), Florida Statute		ns to prop	erly complete a uniform mitigation		
Individuals other than licensed contractors licensed under Section 489.111, Florida Statutes, or professional engineer licensed under Section 471.015, Florida Statutes, must inspect the structures personally and not through employees or other persons. Licensees under s.471.015 or s.489.111 may authorize a direct employee who possesses the requisite skill, knowledge, and experience to conduct a mitigation verification inspection. I, Nick Brugal am a qualified inspector and I personally performed the inspection or (licensed (print name) contractors and professional engineers only) I had my employee (perform the inspection (print name of inspector) and I agree to be responsible for his/her work. Qualified Inspector Signature: Date: 2025-01-13 An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form is subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the appropriate licensing agency or to criminal prosecution. (Section 627.711(4)-(7), Florida Statutes) The Qualified Inspector who certifies this form shall be directly liable for the misconduct of employees as if the authorized mitigation inspector personally performed the inspection. Homeowner to complete: I certify that the named Qualified Inspector or his or her employee did perform an inspection of the residence identified on this form and that proof of identification was provided to me or my Authorized Representative.					
Signature: Date:					
Date.					
An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to w of the first degree. (Section 627.711(7), Florida Statutes)					
The definitions on this form are for inspection purposes on as offering protection from hurricanes.		rtify any	product or construction feature		
Inspectors Initials Property Address 528 Bristle Cone	e Ln, Naples, FL 34113				
*This verification form is valid for up to five (5) years proving course found on the form	ided no material changes h	ave beer	n made to the structure or		

inaccuracies found on the form.

Wind Mitigation Photos

☆ Inspection Notes: Roof Geometry(#RG)

















Wind Mitigation Photos





☆ Inspection Notes:

Secondary Water Resistance(#SWR)



Permit Application Status

PRBD20150928245

In order to view fees or schedule inspections, you need to be signed in.

Summary

Application Number: PRBD20150928245

Application Type: Building Application Status: Finaled

Property Owner's Full Name: REFERENCE ONLY IRONWOOD GROUP ONE A CONDOMINIUM

Category of Work: Alteration/Remodel

Occupancy Code: Assembly, General, Community Halls, Libraries, Museums

Description of Work: REMOVE KITCHEN AND SAUNAS. REBUILD NEW WALL BETWEEN NEW

KITCHEN AND CLOSET 528 BRISTLE CONE LANE

*Clubhouse

Application Date: 09/02/2015
 Issued Date: 09/28/2015
 Expiration Date: 05/11/2016
 Date Finaled: 11/30/2015

1-2 Family or Comm: Commercial

Business Name at Location (Portal)

Business Name: IRONWOOD CLUB HOUSE

Locations

Contacts

Permits (Click to See Reviews)

Deposits & Bonds

Inspections

Conditions

Documents & Images